



RRLKL RRLKS

Features:

 The runner cooling efficiency is improved and pull-out failure is prevented.

Installation Guidelines:

 Effective when runner is thick or when cooling is difficult.

	-L 🖾 :SKH	51 🖪 : 58-60HI	RC			
Code	D	н	В	P	d	
	2 4		2	1.5	1	
	3	5	2	2.3	1.8	
RRLKL	4	6	2.5	2.8	2.3	
RRLAL	5 7		2	2.0	2.8	
	6	8	3	3.8	3	
	8	10	4	5.8	5	

_	@¥/P 0.1mm L14 L19 L25 L30 L35 L40 L45 L50 L60 L70 L80 L90 L100												
D	L14	L19	L25	L30	L35	L40	L45	L50	L60	L70	L80	L90	L100
2													
3													
4													
5													
6													
8													

	-D-L-N 🔼	:SKH51 🚻	: 58-60HRC				
Code	0				4	0.1mm	
Code	U		В		٠	N	
	2	4	2	1.5	1	1.3-3	
	3	3 5		2.3	1.8	2 -5.5	
RRLKS	4	6	2.5	2.8	2.3	2.5-7.5	
RRLRS	5	7	3	3.8	2.8	3.3-9	
	6	8	3	3.0	3	3.3-9	
	8	10	4	5.8	5	5.1-8	

- 0		@¥/P 0.1mm														
U	L14	L19	L25	L30	L35	L40	L45	L50	L60	L70	L80	L90	L100			
2																
3																
4																
5																
6																
8																