



DTR

S1 CATALOG WITH MACHINING ALLOWANCE

**Features:**

1. New cost efficient alternative to other gate inserts and with improved production technology.
2. Moulding and sprue are automatically separated from each other during demoulding.
3. Could be compatible with the I-Mold, Exaflow, Meusburger, HASCO, DME.
4. Variable smaller gate diameters can be carried out in the area of gate

**Installation Guidelines:**

- It is especially suitable for components that have thin walls, such as the mold for TV shell, mobile phone etc.

 Order DTR-0806-S2 **M** :1.3343 (M2) **H** :≈60HRC

Code	D	K	D1	D2	D3	D4	H1	K1	L1	L2	M	@ ¥/P
DTR-0806-S2	8	6	0.6	1.9	3	-	0.6	-	16	3.25	4	
DTR-0808-S2	-	-	0.8	2.1	-	-	-	-	-	-	-	
DTR-1008-S2	10	8	-	2.2	4	3	0.8	4.6	15	4	5	
DTR-1010-S2	-	-	1	2.3	-	-	-	-	-	-	-	
DTR-1012-S2	-	-	1.2	2.6	-	-	-	-	-	-	-	
DTR-1014-S2	-	-	1.4	2.7	-	-	-	-	-	-	-	
DTR-1016-S2	-	-	1.6	3	-	-	-	-	-	-	-	
DTR-1208-S2	12	10	0.8	2.1	5	4	0.8	5.4	14	5	5	
DTR-1210-S2	-	-	1	2.3	-	-	-	-	-	-	-	
DTR-1212-S2	-	-	1.2	2.6	-	-	-	-	-	-	-	
DTR-1214-S2	-	-	1.4	2.7	-	-	-	-	-	-	-	
DTR-1216-S2	-	-	1.6	3	-	-	-	-	-	-	-	
DTR-1218-S2	-	-	1.8	3.1	-	-	-	-	-	-	-	
DTR-1220-S2	-	-	2	3.4	-	-	-	-	-	-	-	
DTR-1412-S2	14	12	1.2	2.5	6	4	0.8	6.4	13	6	6	
DTR-1414-S2	-	-	1.4	2.7	-	-	-	-	-	-	-	
DTR-1416-S2	-	-	1.6	3	-	-	-	-	-	-	-	
DTR-1418-S2	-	-	1.8	3.1	-	-	-	-	-	-	-	
DTR-1420-S2	-	-	2	3.4	-	-	-	-	-	-	-	
DTR-1422-S2	-	-	2.2	3.5	-	-	-	-	-	-	-	
DTR-1424-S2	-	-	2.4	3.8	-	-	-	-	-	-	-	
DTR-1428-S2	-	-	2.8	4.2	-	-	-	-	-	-	-	

